


НЕИЗОЛИРОВАННЫЕ НАКОНЕЧНИКИ

КЛЕММЫ ТИП «О»

Наименование	Габаритные размеры, мм						Сечение провода		
	d2	B	L	E	D	d	мм	мм ²	AWG
1.25-3A	3.2	5.5	11.5	4.5	3.4	1.7	0.57 - 1.44	0.25 - 1.65	22 - 16
1.25-6	6.7	11.6	21.7	4.5	3.4	1.7	0.57 - 1.44	0.25 - 1.65	22 - 16
2-4	4.3	8.5	16.8	4.8	4.0	2.3	1.14 - 1.82	1.04 - 2.63	16 - 14
2-6	6.4	12.0	21.8	4.8	4.0	2.3	1.14 - 1.82	1.04 - 2.63	16 - 14
2-8	8.4	12.0	21.8	4.8	4.0	2.3	1.14 - 1.82	1.04 - 2.63	16 - 14
5.5-4	4.3	9.5	19.8	6.8	5.6	3.5	1.82 - 2.89	2.63 - 6.64	12 - 10
5.5-6	6.4	12.0	25.8	6.8	5.6	3.5	1.82 - 2.89	2.63 - 6.64	12 - 10
5.5-8	8.4	15.0	28.0	6.8	5.6	3.5	1.82 - 2.89	2.63 - 6.64	12 - 10
8-5	5.3	10.0	21.0	8.0	7.0	4.5	2.89 - 3.65	6.64 - 10.52	8
8-8	8.4	14.0	27.0	8.0	7.0	4.5	2.89 - 3.65	6.64 - 10.52	8
14-6	6.4	11.0	25.5	11.0	8.5	5.8	3.65 - 4.62	10.52 - 16.78	6
14-10	10.5	18.0	33.0	11.0	8.5	5.8	3.65 - 4.62	10.52 - 16.78	6



КЛЕММЫ ТИП «U»

Наименование	Габаритные размеры, мм						Сечение провода		
	d2	B	L	E	D	d	мм	мм ²	AWG
1.25-3YS	3.7	5.7	16.0	4.5	3.4	1.7	0.57 - 1.44	0.25 - 1.65	22 - 16
1.25-4YS	4.3	6.4	16.0	4.5	3.4	1.7	0.57 - 1.44	0.25 - 1.65	22 - 16
1.25-6Y	6.7	10.7	17.0	4.5	3.4	1.7	0.57 - 1.44	0.25 - 1.65	22 - 16
2-3YS	3.7	5.7	16.0	4.5	4.0	2.3	1.14 - 1.82	1.04 - 2.63	16 - 14
3.5-5Y	5.3	8.0	18.0	6.3	5.0	3.0	1.82 - 2.4	2.63 - 4.6	12 - 10

